



1. Dimensions in millimetres
2. Tolerance to be $\pm 0.5\%$ unless otherwise stated.
3. Concrete to be grade 50 or grade 40 with air entrainment & in accordance with the department of transport specification.
4. Cover to reinforcement to be min. 25mm. Reinforcement to be in accordance with BS4485: 1989. For bar schedule see drawing EPC-TVCB-004. Bar to be fitted in opposite directions as shown in section C - C (typ. 5 positions).
5. The casting to be permanently marked at top surface as follows:
Manufacturers name, trade mark or other means of identification & date of manufacture (month & year e.g. 5/ 91) & also direction of traffic & indication arrows to be marked as indicated.
6. The overlap of the scarf joint must always be in the direction of traffic flow.

										TITLE Temporary Vertical Concrete Barrier (TVCB) Standard Unit - Reinforcement Elite Product Code : V28					ELITE PRECAST CONCRETE LTD HALESFIELD 9, TELFORD SHROPSHIRE TF7 4QW										
					A	08.02.18	Drawing revised & updated.		CTC	RMD	 	DRN	CTC	CHKD	RMD	DATE	27-09-16	SIZE	A3	SCALE	1:15	DRG	EPC-TVCB-002	REV	A
					O	27.09.16	For Information.		CTC	RMD															
REV	DATE	REASON FOR ISSUE					DRN	APP	REV	DATE	REASON FOR ISSUE					DRN	APP								