1. Handling

Unit Volume / Weight

Unit Ref : **BL3**
Weight : **1125 kg approx.**

Weight is based on 2,350 kg/m³

Lifting system is by means of a 280mm long spherical pin anchor rated at 2.5 tonnes with a safety factor of 3.

Lifting is achieved by use of a 2.5t rated pin anchor ring clutch or combination ring clutch only and should comply with the Lifting Operation & Lifting Equipment Regulations 1998 (LOLER).

Lifting Pin Characteristics

Anchor Type : **T-025-0280**
Anchor Length : **280mm**
dia : **14mm**
Load Class : **2.5 tonnes**

IMPORTANT NOTE :
Prior to lifting older / pre-used blocks, check the lifting pin for wear / corrosion and check the block for cracks. If the block is cracked or the pin is worn, it could fail when lifting.

2. Concrete

Characteristic 28 day cube strength = 50 N/mm² min.
Concrete is Class A1 Fire Resistant in accordance with clause 4.3.4.4 of EN 13369

3. Manufacture

Manufactured to : **BS EN 13369 : 2013**
Tolerances to : **BS EN 13670 : 2009**

4. Physical & Chemical Properties


Appearance : Grey in Colour
Other Chemical Properties : Not Applicable


5. Design


Design Life : **>100 years**


6. Manufacture Tolerances

Length **±5mm**
Width **±5mm**
Height **±5mm**









REV	DATE	REASON FOR ISSUE	DRN	APP
C	18.01.23	Title block & notes updated.	CTC	RMD

TITLE

Duo™ Interlocking Concrete Block
1800mm x 600mm x 450mm (Male / Female Interlocks)
Elite Product Code : **BL3**

ELITE PRECAST CONCRETE LTD
UNIT O, HALESFIELD 9
TELFORD TF7 4QW
Tel : 01952 588885
www.eliteprecast.co.uk
email : sales@eliteprecast.co.uk

DRN	CHKD	DATE	SIZE	SCALE	DRG	REV
CTC	RMD	23-06-16	A4	1:15	BL3	C